

PRO

OFFICE/COMMAND TRAILERS 300C



MODEL	8.5' x 20' NO BATH	8.5' x 20' BATHROOM	8.5' x 24' BATHROOM	8.5' x 28' BATHROOM
All Tube Aluminum Construction	■	■	■	■
Electric Brakes – All Axles	■	■	■	■
(4) 5000# – Scissor Jacks, 7000# Drop Leg Jack	■	■	■	■
16" O/C Floor & Wall Crossmembers, 1" x 3" Roof Studs	■	■	■	■
Extended Triple Tube Tongue	■	■	■	■
Screwless Aluminum Exterior	■	■	■	■
One-piece Aluminum Roof	■	■	■	■
LED Exterior Lights (Clearance, tail lights, loading)	■	■	■	■
32" Door w/Window	■	■	■	■
(2) 15 Amp Exterior Outlets	■	■	■	■
Non-slip Slide-out Step	■	■	■	■
Rear Ramp Door – TPO Floor – Gapless Continuous Hinge	■	■	■	■
Generator Prep Package & Transfer Switch	■	■	■	■
Storage Compartment 48" x 40" x 18"	■	■	■	■
Power Awning w/Lighting	■	■	■	■
(1) 49" x 36" Stand-up Work Table	■	■	■	■
7.5' Interior Height	■	■	■	■
Insulated Walls (R-13) & Ceiling (R-11)	■	■	■	■
50 Amp Breaker Box w/60 Amp Converter	■	■	■	■
Interior Outlets – (4) 15 Amp, (2) 20 Amp Dedicated	■	■	■	■
Furniture Track System	■	■	■	■
Fold-up Sleeper Sofa	■	■	■	■
Aluminum Cabinet Package	■	■	■	■
.9 Cu. Ft. Microwave – 900 W, 4.4 Cu. Ft. Refrigerator – 120v	■	■	■	■
Bathroom	-	■	■	■
36" x 20" Flip-up Work Stations	2	2	3	2
15 Amp Interior Outlets w/USB	2	2	3	2
48" Upper Cabinets	2	2	3	2
42" x 32" Window w/Shade	2	2	3	2
A/C 15,000 BTU w/Thermostat	1	1	2	2
1500W Heater	2	2	2	3
LED 14" Lights	4	4	5	4
5000# Recessed D-Rings	6	6	8	6
Conference Room – 36" x 20" Removable Table, 48" Entrance Door	-	-	-	■

PRO

OFFICE/COMMAND TRAILERS 300C



MODEL	8.5' x 20' NO BATH	8.5' x 20' BATHROOM	8.5' x 24' BATHROOM	8.5' x 28' BATHROOM
Axle Rating (Quantity) lbs/axle	(2) 5200#	(2) 5200#	(2) 5200#	(2) 6000#
GVWR (lbs)	11440	11440	11440	13200
Estimated Base Model Weight (lbs)	4750	5000	5750	6500
Estimated Carry Capacity (lbs)	6690	6440	5690	6700
Axle Type	Torsion	Torsion	Torsion	Torsion
Overall Length	24' 11-3/16"	24' 11-3/16"	28' 11-3/16"	32' 11-3/16"
Overall Width	108 11/16"	108 11/16"	108 11/16"	108 11/16"
Overall Height	10' 10-3/4"	10' 10-3/4"	10' 10-3/4"	10' 10-7/16"
Interior Length	20' 2"	20' 2"	24'-2"	28'-2"
Interior Width	94 7/8"	94 7/8"	94 7/8"	94 7/8"
Interior Height	7' 6"	7' 6"	7' 6"	7' 6"
Minimum Ground Clearance*	12 3/8"	12 3/8"	10 3/8"	10 1/16"
Rear Door Opening Width	90"	90"	90"	90"
Rear Door Opening Height	85"	85"	85"	85"
Tongue Length to Center of Ball	55 9/16"	55 9/16"	55 9/16"	55 9/16"
Center of Coupler to Corner Radius	80 1/4"	80 1/4"	80 1/4"	80 1/4"
Width Between Wheel Wells	83"	83"	83"	81"
Brakes	4 Wheel Electric	4 Wheel Electric	4 Wheel Electric	4 Wheel Electric
Tire Size	ST225/75R15/LRE	ST225/75R15/LRE	ST225/75R15/LRE	T235/80R16/LRE
Hitch Height to Top of Ball	22 3/8"	22 3/8"	22 3/8"	22 1/16"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Floor Crossmembers	16" OC	16" OC	16" OC	16" OC
Wall Studs	16" OC	16" OC	16" OC	16" OC
Ceiling Crossmembers	16" OC	16" OC	16" OC	16" OC
Recommended Generator Rating	12.0 KW	12.0 KW	12.0 KW	12.0 KW
Fresh Water Capacity	50 gal	50 gal	50 gal	50 gal
Waste Water Capacity	42 gal	42 gal	42 gal	45 gal

*To bottom of step or water tank on units with bath

The depictions of trailers in this brochure are for general information purposes only as to the trailers manufactured by ATC during the current model year. Since we continually strive to improve our products, actual products may differ and prices and specifications are subject to change without notice. Product information, specifications, photography, and promotions in this brochure may contain some features that are optional on your trailer. All capacities are approximate and dimensions are nominal. Trailer availability may be limited. ©2022 ATC 5/22